

phyBOARD-Mira



L-809e_4_web_mira_quickstart.pdf

- [phyBOARD® -Mira i.MX 6 Application Guide \(L-806e_1\)](#)

HTML5QuickStart

- https://www.phytec.de/fileadmin/user_upload/downloads/Manuals/L-837e_1_web.pdf

Mira

phyCORE-i.MX6

support@phytec.cn

- [phyCORE-i.MX 6 \(L-808e_2.pdf\)](#)
- sales@phytec.cn
- pin [phyCORE-i.MX6](#)

Linux

- - BSP-Yocto-xxxx-PDxx.x.x.src.mirror.tar.xz [Yocto BSP](#)
 - BSP-Yocto-xxxx-PDxx.x.x.tar.xz
 - image
 - machine.txt yoctomachine ID
- **BSP**BSPimage
- **Yocto**yoctoimage
- QTEclipse

- wiki
 - [Yocto BSP](#)
 - [Qt](#)
 - [phyCORE-i.MX6 NAND/ phyCORE-i.MX6 eMMC linux](#)
 - [/SDK yoctoSDKSDK](#)
 -

	BSP		BSP	Yocto		
PD18.1.2		release note				
PD18.1.1		release note				
PD18.1.0		release note				
PD16.1.2		release note				
PD16.1.1		release note				
PD16.1.0		release note				
PD15.3.1		release note				
PD15.3.0		release note				
PD15.2.0		release note				
PD14.2-rc3		release note				
PD14.2-rc2		release note				

HTML5

	BSP		BSP	Yocto		
v1.0		release note				

Android

	BSP		BSP	
ALPHA1		release note		

WEC2013

		BSP	
BETA1	release note		

BSP		yocto	kernel	Bootloader	QT
PD21.1.0	☒	3.3 Hardknott	linux-mainline v5.10.48-phy2	barebox v2021.04.0-phy4	5.15
PD20.1.0	☐	2.7 Warrior	linux-mainline v4.19.100-phy3	barebox v2019.11.0-phy2	5.12
PD18.1.2	☐	2.4 Rocko	linux-mainline v4.14.134-phy2	barebox v2017.12.0-phy6	5.9
PD18.1.1	☐	2.4 Rocko	linux-mainline v4.14.78-phy2	barebox v2017.12.0-phy3	5.9

PD18.1.0	☐	2.4 Rocko	linux-mainline v4.14.39-phy4	barebox v2017.12.0-phy3	5.9
PD16.1.2	☐	2.1 Krogoth	linux-mainline v4.1.46-phy4	barebox v2016.11.0-phy8	5.6
PD16.1.1	☐	2.1 Krogoth	linux-mainline v4.1.46-phy2	barebox v2016.11.0-phy7	5.6
PD16.1.0	☐	2.1 Krogoth	linux-mainline v4.1.36-phy3	barebox v2016.11.0-phy7	5.6
PD15.3.1	☐	1.8 Fido	linux-mainline v4.1.18-phy5	barebox v2015.11.0-phy4	
PD15.3.0	☐	1.8 Fido	linux-mainline v4.1.18-phy4	barebox v2015.11.0-phy4	
Mira HTML5 v1.0	☒		linux-mainline v4.1.36-phy3	barebox v2016.11.0-phy4	

- git <https://git.phytec.de/>
- manifest <https://git.phytec.de/phy2octo/>
- <https://git.phytec.de/linux-mainline/>
- bootloader <https://git.phytec.de/barebox/>
- layer <https://git.phytec.de/meta-phytec/>
- yoctolinuxlayer <https://git.phytec.de/meta-yogurt/>
- qt demo <https://git.phytec.de/phyRDKDemo/>

[phyCORE SOM](#)

[phyBOARD-Mira](#) [Mira](#)

[phyCORE SOM](#)

[phyBOARD-Mira](#)

[phyCORE-i.MX6](#)

- [phyBOARD-Mira](#)
- [phyBOARD-Nunki](#)
- [phyCORE-i.MX6 Android Power / phyCORE-i.MX6 Android Power Key Setting](#)
- [phyCORE-i.MX6 Android LVDS / phyCORE-i.MX6 Android using LVDS display](#)
- [phyCORE-i.MX6 Android HDMI / phyCORE-i.MX6 Android Enable HDMI output](#)
- [phyCORE-i.MX6 Android / phyCORE-i.MX6 Android change bootanimation](#)
- [phyCORE-i.MX6 Android LinuxeMMCAndroid / phyCORE-i.MX6 Android Flash Android system on eMMC via Linux](#)
- [phyCORE-i.MX6 Android / phyCORE-i.MX6 Android Add never sleep setting](#)
- [phyCORE-i.MX6 Android EC20 R2.0 / Android Add support for EC20 R2.0 4G Module](#)
- [phyCORE-i.MX6 Android eMMC / phyCORE-i.MX6 Android Support eMMC](#)
- [phyCORE-i.MX6 Android NAND / phyCORE-i.MX6 Android how to update nand](#)
- [phyCORE-i.MX6 DualLite eMMC / phyCORE-i.MX6 DualLite eMMC use parallel capacitive touchscreen](#)
- [phyCORE-i.MX6 EIM](#)
- [phyCORE-i.MX6 eMMC linux / phyCORE-i.MX6 eMMC flash linux image](#)
- [phyCORE-i.MX6 HDMI+LVDS/ HDMI+LVDS Dual Display \(same content\)](#)

- [phyCORE-i.MX6 HDMIvga / phyCORE-i.MX6 HDMI-VGA converter setting](#)
 - [phyCORE-i.MX6 NAND/ / phyCORE-i.MX6 update NAND](#)
 - [phyCORE-i.MX6 Q&A](#)
 - [phyCORE-i.MX6 Solo can / phyCORE-i.MX6 Solo adding can interface](#)
 - [phyCORE-i.MX6 i2c / phyCORE-i.MX6 add i2c recovery](#)
 - [phyCORE-i.MX6 / phyCORE-i.MX6 sleep setting](#)
 - [phyCORE-i.MX6 / phyCORE-i.MX6 gigabyte ethernet problem](#)
 - [phyCORE-i.MX6 / add audio support](#)
 - [phyCORE-i.MX6 / Configuration for display](#)
 - [phyCORE-i.MX6 / phyCORE-i.MX6 hardware design info](#)
 - [phyCORE-i.MX6 usbotgnand / phyCORE-i.MX6 Update Nand by USBOTG](#)
 - [phyCORE-i.MX6 machine / phyCORE-i.MX6 config and machine name](#)
 - [phyCORE i.MX6 CPU](#)
 - [phyCORE-i.MX6 SATA](#)
-